POLYGRID-PT2025-GC

FIBRE GLASS GEOCOMPOSITE

PT SERIES GEOCOMPOSITE IS A FIBRE GLASS GEOGRID WITH A POLYMER MODIFIED COATING, BONDED TO A NONWOVEN GEOTEXTILE AND MEETS THE REQUIREMENTS OF EN15381.

| PROPERTY | Metric | Imperial | Test Method |
|-------------------------------------------|--------------------------------|------------------------------------|-------------------------------|
| Tensile strength Ultimate (MD* X CD*) min | 115 X 215 - 15 kN/m | 655 X 1230 - 85 lbs/in | ASTM D6637 EN-ISO 10319 |
| Tensile Elongation Ultimate (MD* X CD*) | 2.5 +/- 1% | 2.5 +/- 1% | ASTM D6637 EN-ISO 10319 |
| Tensile resistance @2% Strain (MD* X CD*) | 95 x 180 +/- 20 kN/m | 542 x 1030 +/- 115 lbs/in | ASTM D6637 EN-ISO 10319 |
| Secant Stiffness EA @1% Strain(MD* X CD*) | 4600 x 8600 +/- 600 N/mm | 26,265 x 49,110 +/- 3425 lbs/in | ASTM D6637 EN-ISO 10319 |
| Young Modulus | 73 GPa | 10.6 x 10 ⁶ psi | |
| Mass per Unit Area | ≥ 835 g/m² | ≥ 24.62 oz/yd² | ASTM D5261 ISO 9864 |
| Asphalt Retention | 0.9 l/m² | 0.2 gal/yd² | ASTM D6140 EN15381 Annex C |
| Melting point of Glass | ≥ 820° C | ≥ 1508° F | ASTM C338 |
| Melting point of Coating | ≥ 232° C | ≥ 450° F | ASTM D276 EN 1SO 3146 |
| Grid Size (Center to Center of Strand) | 12.5 X 12.5 mm / 25 X 19 mm | 0.5 X 0.5 inch / 1 X 0.75 inch | |
| Roll Length | 60 m | 197 ft | |
| Roll Width | 1.5 m | 5ft | |
| Roll Area | 90 m² | 108 yd² | |

- "*" MD: Machine Direction "+" CD: Cross Direction.
- 1. The Grid opening has a 10% tolerance. We can give a different size after understanding the need and discussing with the Technical team.
- 2. The standard roll width is 1.5m but can be given up to 3m maximum. The standard length is 60m but can be altered as per requirement.
- 3. 100% polypropylene nonwoven geotextiles are used in Geocomposite GC, on request we can use other type of nonwoven geotextiles.



ISO 9001: 2015 Certified



www.polyontextiles.com Email:polyon@polyontextiles.com

This data is provided for informational purposes only. Polyon Textiles Pvt Ltd makes no warranties as to the suitability or the fitness for a specific use or merchantability of the products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability from resulting loss or damages. This information is subject to change without notice.